


PATIO DOOR LOCKING BAR BARRE DE SÉCURITÉ (PORTE PATIO)

LOCKING BAR STANDARD INSTALLATION INSTRUCTIONS D'ASSEMBLAGE DE LA BARRE DE SÉCURITÉ

INSTALLATION ON INSIDE SLIDING DOORS

1. Place locking bar on wall next to stationary door.
2. Mark and drill 1/2" hole and secure bracket to wall with screws provided.
- CAUTION: DO NOT DRILL INTO GLASS PANEL.
3. With other end of bar in sliding door, extend bar to inside edge of sliding door, hold in position until screws are tight, and drill 1/2" hole and secure screw through wall into door.




INSTALLATION SUR PORTES coulissantes INTÉRIEURES

1. Place le support à l'intérieur de la porte fixe de la porte fixe.
2. Marquer et percer des trous de 1/2" pour fixer le support au mur et à l'arbre de la porte.
- ATTENTION: NE PAS PERCER DANS LE VITRE DE LA PORTE.
3. Avec l'autre extrémité de la barre dans la porte coulissante, étendre la barre jusqu'à l'extrémité intérieure de la porte coulissante, maintenir la barre en position jusqu'à ce que les vis soient serrées, et percer des trous de 1/2" dans l'arbre de la porte coulissante.

INSTALLATION ON OUTSIDE SLIDING DOORS

Install panel and bracket against inside edge of door frame then holding handle against inside frame of sliding door. Care must be taken that holding handle is positioned at least 1/4" inside edge of the sliding door frame.



INSTALLATION SUR PORTES coulissantes EXTERNES

Place sur le cadre intérieur de la porte fixe. Étendre l'extrémité de la barre jusqu'à l'extrémité intérieure de la porte coulissante, maintenir la barre en position jusqu'à ce que les vis soient serrées, et percer des trous de 1/2" dans l'arbre de la porte coulissante.

TO SCREW

Place screw driver and screw driving portion of bar inside of bar. Place up flush against wall panel.

TO SPACER

Place door and extend sliding portion of bar until end stops into holding cavity.

TO VENTILATE

Place window door and slide door open to desired width. Check with door handle when window frame is present.

POWER WINDOW

Adjustment can be made by disengaging or locking window in position. Disengage by pulling up on the handle of the power bar. Lock window position by pulling down on the handle of the power bar.

POWER WINDOW

Adjustment can be made by disengaging or locking window in position. Disengage by pulling up on the handle of the power bar. Lock window position by pulling down on the handle of the power bar.

POWER WINDOW

Adjustment can be made by disengaging or locking window in position. Disengage by pulling up on the handle of the power bar. Lock window position by pulling down on the handle of the power bar.

SAFETY BLOCK STANDARD INSTALLATION INSTRUCTIONS D'ASSEMBLAGE DU BLOC DE SÉCURITÉ

1. Open sliding panel door.
2. Block is installed in upper channel about 1" from end of track.
3. Place block in place and drill 1/2" hole.
4. Secure block with screw provided.
5. Close panel door. If door block, the top block will push panel.
6. With panel door closed, the top block will push panel into the track.



1. Place panel in place in the door in the upper channel. Adjust to position.
2. Place the block in the upper channel of the track about 1" from the end of the track.
3. Place the block in the track and drill 1/2" hole.
4. Secure the block with the screw provided.
5. Close the panel door. If the door block, the top block will push panel into the track.
6. With panel door closed, the top block will push panel into the track.